Seating » Seats



Collection: Verge

Seating » Seats



Seating » Seats



Simple, durable seat design. Batten top in 2 hardwood or 4 Duraslat™ colors with steel posts and base plates in 17 powder-coat or galvanized finishes.

Description

The Verge seat is simple in design and highly durable. Hardwood or Duraslat™ battens work with cylindrical steel posts and circular base plates to add a functional and utilitarian feel to spaces you know are going to get their fair share of wear and tear. Finishes include 2 Australian Eucalyptus hardwood or 4 Duraslat™ colors and 17 powdercoat finishes or a galvanized finish.

Made In

USA

Dimensions

71"W x 21"D x 32"H

(1800mmW x 530mmD x 820mmH)

 $83"W \times 21"D \times 32"H$

(2100mmW x 530mmD x 820mmH)

Seat height: 18" (455mm)

Seating » Seats

Weight Hardwood

71′′W

96.8lbs (44kg)

83"W

112.2lbs (51kg)

Duraslat™ 71″W

90.2lbs (41kg)

83"W

99lbs (45kg)

Batten Type Hardwood

Australian Eucalyptus

Duraslat™

Plateau, Summit, Canyon, Outback

Frame Powder-coated steel or galvanized steel

Powder Coat Core

Coreten (textured), Charcoal (satin), Silver Pearl (satin metallic), Black

(satin), White (satin), Bronze (satin metallic)

Signature

Deep Ocean (satin), Wedgewood (satin), Mangrove (satin), Territory Red

(matt), Claypot (satin), Paperbark (satin)

Bold

Sky Blue (satin), Yellow Green (satin), Pure Orange (satin), Carmine Red

(satin), Zinc Yellow (satin

Seating » Seats

Sustainability Certified Hardwood

Australian Eucalyptus hardwood is sourced from sustainable forests certified by the Program for the Endorsement of Forest Certification (PEFC), the world's largest forestry certification system.

Material Alternatives

We offer sustainable alternatives to hardwood, such as Duraslat™; a mineral-based composite material that contains no Volatile Organic Compounds (VOCs) and is engineered using up to 46% natural filler that is based on a renewable mineral.

Recycled Materials

We locally source our steel. It means we know it uses recycled content and is 100% recyclable.

Low Pollutants

Our powder-coating process doesn't emit VOCs and has Environmental Product Declarations (EPDs) that enable projects to qualify for LEED credits

Warranty	5-year warranty.	View the warranty	for more details.
----------	------------------	-------------------	-------------------

Lead Time 6-8 weeks

Assembly & Delivery Shipped fully assembled on pallets.

Fixing Detail Post fixed by others - must be surface fixed.

Anchors not included.

How to Specify Select your length

Select your batten finish Select your frame finish Select your fixing type

Seating » Seats

Care Instructions

<u>Hardwood</u>

Cleaning

Remove any loose surface deposits with a soft bristled brush and wipe down with fresh water and a non-abrasive cloth.

Oilina

Oiling of timber will postpone natural greying, repel moisture, improve mould resistance, help maintain a smooth surface texture and enhance the grain and colour.

To maintain, lightly sand rough areas of timber and brush on one coat of timber decking oil every 6 months or as required.

Duraslat™

Cleaning

Clean with mild soap and water and use a soft brush to remove any dirt build-up.

Powder-Coat

Cleaning

Carefully remove any loose surface deposits with a wet sponge or soft bristled brush.

Use a soft (non-abrasive) cloth or brush and a diluted solution of mild detergent and warm water.

Ensure surfaces are thoroughly rinsed with clean fresh water after cleaning to remove all residues.

Never use thinners, abrasive cleaning agents, alcohol-based, acid or alkali cleaning agents.

Additional Comments

Hardwood is treated with a UV-resistant oil finish in a light or dark tone.