Seating » Seats




Collection: Avenue

Seating » Seats



Seating » Seats



Minimalist platform seating with half a back. 2 hardwood or 4 Duraslat™ batten colors. Tapered steel frame in 17 powder-coat or galvanized finishes.

Description

Rectangular battens and a tapered steel frame combine to deliver a minimalist seating design that takes its cues from 20th century industrial design. The functional feel and light appearance of the Avenue platform seat complement and sits within most public spaces. Finishes include 2 Australian Eucalyptus hardwood or 4 Duraslat™ colors and 17 powdercoat finishes or a galvanized finish.

Made In USA

Dimensions 95" W x 23"D x 33"H

(2400mmW x 580mmD x 830mmH)

Seat height: 18" (460mm)

Weight Hardwood

95"W

178lbs (81kg)

Duraslat™ 95″W

147lbs (67kg)

Seating » Seats

Batten Type Hardwood

Australian Eucalyptus

Duraslat™

Plateau, Summit, Canyon, Outback

Powder-coated or galvanized steel Frame

Powder Coat Core

Coreten (textured), Charcoal (satin), Silver Pearl (satin metallic), Black

(satin), White (satin), Bronze (satin metallic)

Signature

Deep Ocean (satin), Wedgewood (satin), Mangrove (satin), Territory Red

(matt), Claypot (satin), Paperbark (satin)

Bold

Sky Blue (satin), Yellow Green (satin), Pure Orange (satin), Carmine Red

(satin), Zinc Yellow (satin)

Certified Hardwood Sustainability

Australian Eucalyptus hardwood is sourced from sustainable forests

certified by the Program for the Endorsement of Forest Certification

(PEFC), the world's largest forestry certification system.

Material Alternatives

We offer sustainable alternatives to hardwood, such as Duraslat™; a mineral-based composite material that contains no Volatile Organic Compounds (VOCs) and is engineered using up to 46% natural filler that

is based on a renewable mineral.

Recycled Materials

We locally source our steel. It means we know it uses recycled content

and is 100% recyclable.

Low Pollutants

Our powder-coating process doesn't emit VOCs and has Environmental

Product Declarations (EPDs) that enable projects to qualify for LEED

credits.

Warrantv 5-year warranty. View the warranty for more details.

Lead Time 6-8 weeks

Assembly & Delivery Shipped fully assembled on pallets.

Seating » Seats

Fixing Detail Surface or sub-surface fixed by others.

Anchors not included.

Shims available for sub-surface fixing on request.

How to Specify Select your batten colour

Select your frame finish Select your fixing type

Care Instructions

Hardwood

Cleaning

Remove any loose surface deposits with a soft bristled brush and wipe down with fresh water and a non-abrasive cloth.

Oiling

Oiling of timber will postpone natural greying, repel moisture, improve mould resistance, help maintain a smooth surface texture and enhance the grain and colour.

To maintain, lightly sand rough areas of timber and brush on one coat of timber decking oil every 6 months or as required.

Duraslat™

Cleaning

Clean with mild soap and water and use a soft brush to remove any dirt build-up.

Powder-Coat

Cleaning

Carefully remove any loose surface deposits with a wet sponge or soft bristled brush.

Use a soft (non-abrasive) cloth or brush and a diluted solution of mild detergent and warm water.

Ensure surfaces are thoroughly rinsed with clean fresh water after cleaning to remove all residues.

Never use thinners, abrasive cleaning agents, alcohol-based, acid or alkali cleaning agents.

Additional Comments

Hardwood is treated with a UV-resistant oil finish in a light or dark tone.