Seating » Benches



Collections: Connect















Seating » Benches

Modern, modular, circular bench seating in a medium low size with hardwood battens and a steel frame in powder-coat colors.

110000	'n	٠+،	\sim r	•
Descr		ιl	OI.	ı

Connect circle medium low modular bench seating is versatile, durable. and sustainable, making it suitable for a wide range of outdoor or indoor spaces. This can be used as a stand-alone module or paired with the range of 18 seating modules, consisting of geometric shapes, and interlocking elements that can transform any public space into a social hub. Connect features certified Australian Eucalyptus hardwood battens with bullnose edging and a steel frame in VOC-free powder-coat colours that can be customized to suit your project.

How to Specify

Select your batten finish Select your frame finish

Sustainability

Certified Hardwood

Australian Eucalyptus hardwood is sourced from sustainable forests certified by the Program for the Endorsement of Forest Certification (PEFC), the world's largest forestry certification system.

Recycled Materials

We locally source our steel. It means we know it uses recycled content and is 100% recyclable.

Low Pollutants

Our powder-coating process doesn't emit VOCs and has Environmental Product Declarations (EPDs) that enable projects to qualify for LEED credits.

Powder Coat

Core

Signature

Bold

Dimensions

85"W x 45"D x 18"H

(2160mmW x 1155mmD x 450mmH)

Batten Type

Class 1 + Select Grade Hardwood: Australian Eucalyptus with bullnose

edging

Frame

Powder-coated steel

Weight

357lbs (162.1kg)

Made In	USA	
Lead Time	6-8 weeks	
Assembly & Delivery	Shipped fully assembled on pallets.	
Fixing Detail	Fixed by others. Fix direct to a concrete slab or through pavers and into a concrete slab.	
	Depending on the location, the seating modules can be placed without them being fixed to a slab.	
Care Instructions	Hardwood Cleaning Remove any loose surface deposits with a soft bristled brush and wipe down with fresh water and a non-abrasive cloth.	
	Oiling Oiling of timber will postpone natural greying, repel moisture, improve mould resistance, help maintain a smooth surface texture and enhance the grain and colour.	
	To maintain, lightly sand rough areas of timber and brush on one coat of timber decking oil every 6 months or as required.	
	Powder-Coat Cleaning Carefully remove any loose surface deposits with a wet sponge or soft bristled brush.	
	Use a soft (non-abrasive) cloth or brush and a diluted solution of mild detergent and warm water.	
	Ensure surfaces are thoroughly rinsed with clean fresh water after cleaning to remove all residues.	
	Never use thinners, abrasive cleaning agents, alcohol-based, acid or alkali cleaning agents.	
Warranty	5-year warranty. View the <u>warranty</u> for more details.	
Additional Comments	Hardwood is treated with a UV-resistant oil finish in a light or dark tone.	

Seating » Benches

Colour & Finish Options